



# STOP! READ BEFORE USE!



PATENTED - STAYBULLTOOLS.COM/IP



# STAYBULL MULTI-BASE™ SAFETY & USAGE GUIDELINES

**FAILURE TO READ AND FOLLOW ALL SAFETY INSTRUCTIONS MAY  
RESULT IN SERIOUS INJURY OR DEATH.**


**THE STAYBULL MULTI-BASE™ IS NOT A FALL-ARREST OR FALL-PREVENTION DEVICE.  
USER ASSUMES ALL RISK.**

The STAYBULL MULTI-BASE™ is engineered to enhance stability when used correctly, but it must always be operated in accordance with ladder manufacturer instructions, jobsite safety requirements, and the guidelines below. No stability device can eliminate all risk.

**375**  
lbs MAX



**USE ONLY  
ON CLEAN,  
DRY, STABLE  
SURFACES**



**CHOOSE THE  
CORRECT  
TRACTION PAD  
FOR THE JOB**

## 1. INSPECT BEFORE EACH USE

- ✓ Inspect the **STAYBULL MULTI-BASE™** and **all traction pads** for cracks, wear, deformation, or missing components.
- ✓ **DO NOT USE** the product if any part is **damaged, loose, or missing**.
- ✓ **Replace** worn traction pads immediately.
- ✓ Confirm that **all surfaces** of the MULTI-BASE™ are **clean** and free of oil, mud, snow, or debris.
- ✓ Users are responsible for ensuring the product is in a **safe working condition before every use**.

By using the STAYBULL MULTI-BASE™, the user agrees that STAYBULL TOOLS® and all affiliated entities are not liable for any injury or loss arising from improper use, misuse, unsafe ladder practices, or failure to follow instructions. The user assumes all risks associated with ladder use and jobsite hazards. Use of the product constitutes acceptance of these terms.

## 2. SURFACE CONDITIONS FOR SAFE OPERATION

- ✓ Use only on **clean, dry, stable surfaces**. Traction pads may not function properly if wet, dirty, icy, oily, or contaminated. Clean metal surfaces before use.
- ✓ **DO NOT USE** on **excessively steep, slippery, unstable, or debris-covered surfaces**.
- ✓ Jobsite conditions can change rapidly; **reassess traction and stability frequently**.
- ✓ **Extreme** temperatures, moisture, and weather **conditions may reduce traction and overall performance**.
- ✓ **If adequate traction cannot be achieved, DO NOT USE the device.**

**CONTINUED ON PAGE 2**





# STAYBULL MULTI-BASE™ GUIDELINES CONTINUED

## 3. PROPER USE

- Supports extension and straight ladders.
- Supports materials and tools.
- Provides a stable working platform on sloped or uneven ground.
- Supports up to **375 lbs** (combined user + tools) on flat, appropriate surfaces.
- Stability on sloped surfaces depends on pitch, conditions, pad type, and proper ladder setup.
- Confirm adequate grip between the traction pads and the surface before climbing.
- Ensure ladder feet rest fully and securely within the designated contact areas.
- **USE ONLY AS INTENDED.** Follow all jobsite, ladder setup, and roof-access safety guidelines.
- Misuse, improper setup, or unsafe operation may result in injury.

The MULTI-BASE™ does not compensate for improper ladder setup or unsafe climbing practices.

**\*\*NOT INTENDED FOR EVERY APPLICATION\*\***

## 4. DIRECTIONS FOR USE

### PREPARE

Choose the correct traction pad for the job:



**Black General-Purpose Pad**  
Durable and long-lasting for most surfaces.





**Gray Metal Roofing Pad**  
Specifically designed for metal roofing applications.

Replace traction pads when worn or damaged.

### PLACEMENT

Position the MULTI-BASE™ only on **stable, clean, and dry** surfaces. For sloped surfaces, orient the tool using the correct side to create a level base. Keep your weight centered and avoid leaning uphill.



### STABILITY CHECK

- Before fully loading the device, apply light downward pressure to confirm traction.
- **If any slipping, shifting, or movement occurs, DO NOT USE the device.**

### LADDER SETUP

- Ensure ladder feet fit securely within the designated areas.
- Follow all ladder manufacturer instructions and OSHA/ANSI ladder safety guidelines.
- A spotter may be required depending on jobsite conditions.

### AFTER USE & STORAGE

- Store the MULTI-BASE™ in a clean, cool, dry environment.
- Clean traction pads with mild soap and water; allow to fully air-dry before next use.
- Do not store in direct sunlight or extreme temperatures for prolonged periods.

## 5. USER RESPONSIBILITY

By using the STAYBULL MULTI-BASE™, the user acknowledges:

- They have read and understand all safety instructions.
- They are responsible for proper ladder setup and safe operation.
- They will use the product only as intended and only under safe conditions.
- They understand that no device can eliminate all risk of slips, falls, or instability.

## 6. REPLACEMENT LABELS AND PARTS

**THE SAFETY LABEL MUST BE REPLACED IF DAMAGED, WORN, OR ILLEGIBLE.** Replacement traction pads, labels, and components are available at [STAYBULLTOOLS.COM](http://STAYBULLTOOLS.COM)

By using the STAYBULL MULTI-BASE™, the user agrees that STAYBULL TOOLS® and all affiliated entities are not liable for any injury or loss arising from improper use, misuse, unsafe ladder practices, or failure to follow instructions. The user assumes all risks associated with ladder use and jobsite hazards. Use of the product constitutes acceptance of these terms.